

# ROTARY DRUM DRYER

■ STABLE AND ENERGY-SAVING ROTARY DRUM DRYER



delivers stable performance  
and can efficiently process  
a wide range of materials  
continuously.

## ■ Product Display







SPECIFICATION (M) (DIAMETER × LENGTH)	DRUM VOLUME (M <sup>3</sup> )	CAPACITY (T/H)	INSTALLATION SLOPE (%)	MAX INLET TEMPERATURE (°C)	MAIN MOTOR (KW)
Φ1.2×8.0	9	1.9-2.4	3-5	700-800	7.5
Φ1.2×10	11.3	2.4-3.0	3-5	700-800	7.5
Φ1.5×12	21.2	4.5-5.7	3-5	700-800	15
Φ1.5×14	24.7	5.3-6.6	3-5	700-800	15
Φ1.5×15	26.5	5.7-7.1	3-5	700-800	15
Φ1.8×12	30.5	6.5-8.1	3-5	700-800	18.5
Φ1.8×14	35.6	7.6-9.5	3-5	700-800	18.5
Φ2.2×12	45.6	9.7-12.2	3-5	700-800	22
Φ2.2×14	53.2	11.4-14.2	3-5	700-800	22
Φ2.2×16	60.8	13.0-16.2	3-5	700-800	22

# FAQ

## ■ Are your dryers suitable for handling sticky materials?

For high-moisture and sticky materials, our dryers can be equipped with a breaking device to effectively prevent wet materials from sticking to the walls, ensuring smooth drying.

## ■ What types of rotary drum dryers do you offer?

We offer mainly single-cylinder dryers, which are suitable for a variety of materials. We can also customize two-stage or three-stage dryers to improve thermal efficiency and space utilization based on your specific needs.

## ■ Is the maintenance of your equipment complex?

Our equipment is designed for simplicity and durability, making maintenance easy. Routine checks and cleaning of vulnerable parts are all that's needed.

## ■ How can I determine if the dryer's capacity meets my needs?

Choose the appropriate model based on your materials' moisture content, feed rate, and required drying time. Alternatively, contact our technical team for a customized solution.

Zhengzhou Kawise Technology Co., Ltd.

Website | <https://www.kawise.com/>

Email | [info@kawise.com](mailto:info@kawise.com)

Mobile | +86 187 0382 0393

Whatsapp | +86 187 0382 0393