

SKIRTED BELT CONVEYOR

■ RELIABLE TRANSPORT FOR PELLETS
AND SMALL MATERIALS



features a simple structure,
ensuring easy maintenance
and reliable operation.

■ Product Display





ATTRIBUTES

Skirt Belt Width

Conveying Length

Belt Speed

Conveying Capacity

Conveying Angle

Power

RANGE

200-1400mm

3m-20m

0.5m/s-3m/s

1t/h-100t/h

15°- 45°

0.75KW-30KW

FAQ

■ What is the difference between a sidewall belt conveyor and a screw conveyor?

A sidewall belt conveyor is designed for handling granular materials with an open structure, while a screw conveyor is ideal for sealed transport of powder materials, offering better dust control.

■ Can the conveying speed be adjusted?

The conveyor operates at a fixed speed by default, but a variable frequency control system can be added for flexible speed adjustment.

■ What types of layouts does this conveyor support?

Our conveyor supports various layout configurations, including straight, inclined, L-shaped, and Z-shaped orientations. It can be customized to optimize space usage based on actual site conditions.

■ How do I clean and maintain the conveyor?

The conveyor belt has a smooth surface, making it easy to clean with water or neutral detergent. The drive components require only routine checks for tension and lubrication.

Zhengzhou Kawise Technology Co., Ltd.

Website | <https://www.kawise.com/>

Email | info@kawise.com

Mobile | +86 187 0382 0393

Whatsapp | +86 187 0382 0393